



NATA LIGHTING CO.,LTD
www.nata.cn
Email:info@nata.cn
Tel:+86 0750-377 0000(10 lines) Fax:+86 0750-377 1111
Address:380JinOu Road,Gaoxin Zone,Jiang Men City,Guangdong,China

NT

Client: NT

LumCAT: 1-1703-LM2

Luminaire: 92.70.481.00 LED HOLDER

Report No: 20251217-B021

Ballast type: AC

Test No: 20251217-C021

Voltage(V): 35.070

LampCAT: CITIZEN CLU028 LES9.8

Current(A): 0.361

Lamp flux(lm): 1498.0

Power (W): 12.660

Number of Lamps: 1

PF: 0.000

Length(mm): 50

Width(mm): 50

Phm Type: C

Height(mm): 22

Photometric Results

Lumens(lm): 1438.15, Efficiency(%): 96.00% , Luminous Efficacy(lm/W): 113.60

Central intensity(cd): 5560.537, Maximum intensity(cd): 5560.537

Angle of maximum intensity: C=0.0 γ =0.0

Beam Angle(50%Imax): [C0/180]Total=17.8

[C90/270]Total=17.8

Field angle(10%Imax): [C0/180]Total=56.6

[C90/270]Total=56.6

Maximum s/h(1/2): C0_180=0.30 C90_270=0.30

Maximum s/h(1/4): C0_180=0.34 C90_270=0.34

Up flux rate of lamp(%): 0.00%


Down flux rate of lamp(%): 96.00%


Up flux rate of LUM(%): - -


Down flux rate of LUM(%): 100.00%

CIE Type : Direct lighting

Output flux ratio in π solid angle : 99.571%









House

[Unit:cd]

Road

Imax:5560.54	
(10%Imax) 556.054	
(20%Imax) 1112.11	
(30%Imax) 1668.16	
(40%Imax) 2224.21	
(50%Imax) 2780.27	
(60%Imax) 3336.32	
(70%Imax) 3892.38	
(80%Imax) 4448.43	
(90%Imax) 5004.48	





Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	83591	17808	8297	4573	3101	2492	2478	3045	4034
C45	83591	17808	8297	4573	3101	2492	2478	3045	4034
C90	83591	17808	8297	4573	3101	2492	2478	3045	4034

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
3101	3101	3101	2478	2478	2478	4034	4034	4034

Glare Table


Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve




Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	23.08	24.09	23.45	24.40	24.72	23.35	24.36	23.71	24.67	24.99
	3H	22.89	23.78	23.27	24.12	24.47	23.15	24.05	23.54	24.38	24.73
	4H	22.79	23.62	23.19	23.97	24.34	23.05	23.88	23.45	24.23	24.60
	6H	22.71	23.46	23.12	23.84	24.24	22.97	23.72	23.39	24.10	24.50
	8H	22.63	23.35	23.05	23.74	24.15	22.90	23.62	23.32	24.00	24.41
	12H	22.57	23.25	22.99	23.64	24.06	22.83	23.51	23.25	23.90	24.32
4H	2H	22.79	23.61	23.19	23.97	24.33	23.05	23.88	23.45	24.23	24.60
	3H	22.56	23.24	22.98	23.64	24.06	22.82	23.51	23.25	23.90	24.32
	4H	22.49	23.08	22.93	23.50	23.95	22.75	23.34	23.19	23.77	24.21
	6H	22.36	22.88	22.83	23.33	23.78	22.62	23.14	23.09	23.59	24.04
	8H	22.30	22.78	22.79	23.24	23.72	22.56	23.04	23.05	23.50	23.98
	12H	22.26	22.70	22.75	23.15	23.67	22.51	22.96	23.00	23.41	23.93
8H	4H	22.29	22.78	22.78	23.23	23.71	22.56	23.04	23.04	23.50	23.97
	6H	22.15	22.55	22.66	23.03	23.54	22.41	22.81	22.92	23.29	23.80
	8H	22.15	22.48	22.68	23.00	23.50	22.40	22.74	22.94	23.26	23.76
	12H	22.10	22.36	22.64	22.88	23.40	22.35	22.61	22.89	23.13	23.65
12H	4H	22.24	22.69	22.73	23.14	23.66	22.51	22.95	23.00	23.40	23.92
	6H	22.14	22.47	22.67	23.00	23.49	22.40	22.73	22.93	23.25	23.75
	8H	22.10	22.36	22.64	22.87	23.40	22.35	22.61	22.89	23.13	23.65
Variation with the observer position at spacings:											
S = 1.0H		3.3/-13.5					3.3/-13.5				
S = 1.5H		5.3/-15.5					5.3/-15.5				
S = 2.0H		7.3/-15.4					7.3/-15.4				
Standard tables:		BK0					BK0				
Uncorrected UGR		4.4					4.4				

UGR calculation is based on CIE Publ. 117 ,S/H = 0.25



RHOCC	80			70			50			30			10			0
RHOW	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	COEFFCIENTS OF UTILIZATION RHOFC=20 CU															
0	1.14	1.14	1.14	1.12	1.12	1.12	1.07	1.07	1.07	1.02	1.02	1.02	0.98	0.98	0.98	0.96
1	1.07	1.05	1.03	1.05	1.03	1.01	1.01	0.99	0.98	0.97	0.96	0.95	0.94	0.93	0.92	0.91
2	1.00	0.96	0.93	0.98	0.95	0.92	0.95	0.93	0.90	0.92	0.90	0.88	0.90	0.88	0.87	0.85
3	0.94	0.89	0.86	0.93	0.89	0.85	0.90	0.87	0.84	0.88	0.85	0.83	0.86	0.83	0.81	0.80
4	0.88	0.84	0.80	0.87	0.83	0.79	0.85	0.81	0.78	0.83	0.80	0.77	0.82	0.79	0.77	0.75
5	0.83	0.78	0.75	0.83	0.78	0.74	0.81	0.77	0.74	0.79	0.76	0.73	0.78	0.75	0.72	0.71
6	0.79	0.74	0.70	0.78	0.73	0.70	0.77	0.73	0.69	0.76	0.72	0.69	0.74	0.71	0.68	0.67
7	0.75	0.70	0.66	0.74	0.69	0.66	0.73	0.69	0.66	0.72	0.68	0.65	0.71	0.68	0.65	0.64
8	0.71	0.66	0.63	0.71	0.66	0.63	0.70	0.65	0.62	0.69	0.65	0.62	0.68	0.64	0.62	0.61
9	0.68	0.63	0.60	0.68	0.63	0.59	0.67	0.62	0.59	0.66	0.62	0.59	0.65	0.62	0.59	0.58
10	0.65	0.60	0.57	0.65	0.60	0.57	0.64	0.60	0.57	0.63	0.59	0.56	0.63	0.59	0.56	0.55



Luminaire Lumens:

FL=488.33,FM=204.2,FH=2.38,FVH=0.46

BL=524.69,BM=217.07,BH=2.78,BVH=0.49

UL=0,UH=0

BUG Rating:B2-U0-G0

Intensity data(cd)

C/γ(°)	0.0	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0
0.0	5503.44	5403.32	5149.63	4787.94	4340.19	3764.76	3308.57	2895.13	2455.26
45.0	5601.32	5551.26	5415.13	5172.69	4973.01	4483.07	4024.07	3569.57	3151.63
90.0	5567.01	5451.69	5174.38	4824.51	4389.13	3814.26	3532.44	3098.76	2708.94
135.0	5570.38	5583.32	5550.13	5381.94	5123.76	4751.94	4299.13	4010.01	3428.38
180.0	5503.44	5604.69	5588.38	5488.82	5289.69	5113.63	4641.69	3992.57	3712.44
225.0	5601.32	5550.69	5479.82	5160.32	4708.63	4446.51	3975.13	3515.57	3092.01
270.0	5567.01	5598.51	5547.32	5475.32	5215.44	4870.07	4434.69	3955.44	3668.57
315.0	5570.38	5469.69	5268.32	4885.82	4638.32	3974.01	3392.38	3117.32	2698.82
360.0	5503.44	5403.32	5149.63	4787.94	4340.19	3764.76	3308.57	2895.13	2455.26
C/γ(°)	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0
0.0	2257.26	1968.13	1733.01	1541.76	1344.32	1101.49	1101.49	1002.99	951.13
45.0	2918.19	2350.07	2046.32	1890.51	1631.19	1450.63	1301.57	1177.26	1110.88
90.0	2365.26	2017.07	1873.07	1669.44	1491.13	1338.69	1052.33	1052.33	1015.71
135.0	2987.94	2595.32	2184.69	1910.19	1695.88	1515.88	1417.44	1243.07	1124.38
180.0	3268.63	2787.69	2423.76	2099.76	1934.94	1669.44	1491.69	1330.26	1190.76
225.0	2630.76	2415.88	2084.01	1799.38	1578.88	1370.19	1103.06	1103.06	1002.71
270.0	3129.13	2561.57	2343.32	2027.19	1726.82	1531.07	1360.07	1268.38	1115.94
315.0	2323.07	2005.26	1710.51	1592.94	1417.44	1099.46	1099.46	1038.71	952.71
360.0	2257.26	1968.13	1733.01	1541.76	1344.32	1101.49	1101.49	1002.99	951.13
C/γ(°)	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0
0.0	877.67	816.13	763.76	710.49	674.44	642.49	609.30	599.46	571.16
45.0	993.32	908.38	839.76	781.82	750.88	698.01	659.19	625.44	591.69
90.0	918.84	878.06	796.84	743.12	727.09	684.79	655.59	628.09	599.91
135.0	1027.07	945.51	906.13	819.51	777.32	756.51	718.26	686.19	655.82
180.0	1121.01	1001.19	920.19	853.82	787.44	768.32	704.76	674.38	656.94
225.0	950.18	843.81	804.43	743.79	680.96	635.23	594.17	554.46	536.51
270.0	1009.63	923.57	852.13	815.57	755.94	698.01	677.76	641.76	631.07
315.0	882.23	812.36	783.45	741.04	707.79	673.31	648.73	634.73	602.21
360.0	877.67	816.13	763.76	710.49	674.44	642.49	609.30	599.46	571.16
C/γ(°)	27.0	28.0	29.0	30.0	31.0	32.0	33.0	34.0	35.0
0.0	552.09	536.46	518.85	511.37	500.91	489.15	478.46	463.22	455.57
45.0	566.38	543.88	523.63	512.94	492.69	478.63	464.57	451.63	433.63
90.0	587.42	568.07	550.46	534.43	516.71	508.39	495.06	470.08	461.14
135.0	627.69	612.51	585.51	565.26	547.26	530.94	521.38	505.07	483.69
180.0	624.88	600.13	581.01	563.57	552.88	537.13	524.19	512.94	496.63
225.0	510.53	488.31	468.84	449.78	442.07	433.29	419.01	413.16	406.63
270.0	596.19	574.26	562.44	543.32	530.38	517.44	507.88	502.26	488.19
315.0	577.41	565.88	547.26	530.72	515.87	499.89	491.91	476.49	461.36
360.0	552.09	536.46	518.85	511.37	500.91	489.15	478.46	463.22	455.57
C/γ(°)	36.0	37.0	38.0	39.0	40.0	41.0	42.0	43.0	44.0
0.0	436.73	407.81	388.86	352.97	312.98	269.94	217.35	191.03	147.99
45.0	424.07	412.26	395.94	370.63	341.94	307.63	307.63	284.57	188.04
90.0	448.14	430.20	403.26	361.97	338.85	298.35	256.61	212.63	162.28
135.0	474.13	457.26	439.82	412.26	380.76	358.26	310.44	293.57	293.57
180.0	480.32	465.69	449.38	435.88	400.44	364.44	323.94	281.19	281.19
225.0	404.04	392.68	369.34	352.29	318.09	279.34	237.32	190.46	166.95
270.0	473.01	458.94	434.19	406.63	371.76	332.94	308.76	308.76	206.33
315.0	447.08	418.44	387.51	351.23	303.86	279.23	236.87	193.05	151.14
360.0	436.73	407.81	388.86	352.97	312.98	269.94	217.35	191.03	147.99

Intensity data(cd)

C/ γ (°)	45.0	46.0	47.0	48.0	49.0	50.0	51.0	52.0	53.0
0.0	108.34	74.48	43.99	34.82	26.72	23.91	19.80	16.48	13.33
45.0	149.91	128.48	89.89	63.11	43.76	32.68	28.91	22.56	16.26
90.0	137.98	100.46	67.22	38.48	26.61	23.06	20.59	17.78	16.37
135.0	180.28	138.94	100.18	65.81	49.11	25.93	18.06	16.37	14.23
180.0	190.63	147.99	124.03	81.90	54.73	37.01	28.13	24.47	21.26
225.0	130.56	97.71	66.21	47.14	36.79	31.84	27.00	24.24	19.80
270.0	181.07	133.09	97.14	66.99	45.34	37.80	30.88	27.96	23.79
315.0	103.39	81.56	40.50	29.08	19.18	16.71	14.68	12.77	10.86
360.0	108.34	74.48	43.99	34.82	26.72	23.91	19.80	16.48	13.33
C/ γ (°)	54.0	55.0	56.0	57.0	58.0	59.0	60.0	61.0	62.0
0.0	10.58	8.10	7.26	6.53	5.79	5.06	4.39	3.94	3.43
45.0	14.01	10.86	8.10	6.47	5.57	5.29	4.67	4.39	4.16
90.0	13.95	11.76	10.01	8.38	7.71	6.13	5.23	5.01	4.33
135.0	13.61	11.70	9.62	8.89	7.76	6.98	6.24	5.51	5.23
180.0	18.17	16.48	13.73	11.81	10.18	9.06	8.33	7.03	6.08
225.0	15.86	12.60	9.73	8.61	7.26	6.30	5.57	4.95	4.50
270.0	19.41	15.08	12.66	10.69	9.79	8.16	7.14	6.13	5.34
315.0	9.96	8.61	7.31	6.36	5.40	4.84	4.16	3.32	3.04
360.0	10.58	8.10	7.26	6.53	5.79	5.06	4.39	3.94	3.43
C/ γ (°)	63.0	64.0	65.0	66.0	67.0	68.0	69.0	70.0	71.0
0.0	3.09	2.87	2.59	2.36	2.19	1.97	1.86	1.74	1.63
45.0	3.88	3.83	3.49	3.43	3.26	3.15	3.15	3.04	2.93
90.0	3.77	3.43	2.98	2.81	2.48	2.25	2.03	1.74	1.69
135.0	4.67	4.22	3.77	3.26	2.81	2.36	2.08	1.97	1.74
180.0	5.29	4.73	4.39	3.77	3.43	3.26	2.93	2.70	2.48
225.0	4.05	3.66	3.49	3.26	3.04	2.81	2.64	2.53	2.48
270.0	4.89	4.16	3.66	3.32	2.98	2.76	2.31	2.08	1.91
315.0	2.59	2.36	1.86	1.63	1.46	1.41	1.29	1.24	1.24
360.0	3.09	2.87	2.59	2.36	2.19	1.97	1.86	1.74	1.63
C/ γ (°)	72.0	73.0	74.0	75.0	76.0	77.0	78.0	79.0	80.0
0.0	1.52	1.41	1.35	1.35	1.24	1.24	1.13	1.13	1.13
45.0	2.87	2.70	2.70	2.59	2.53	2.53	2.42	2.36	2.19
90.0	1.41	1.29	1.29	1.24	1.13	1.13	1.07	1.07	0.96
135.0	1.58	1.41	1.35	1.29	1.24	1.24	1.18	1.18	1.07
180.0	2.31	2.19	2.03	1.86	1.80	1.74	1.74	1.63	1.58
225.0	2.19	2.08	2.03	2.03	1.91	1.86	1.80	1.74	1.63
270.0	1.69	1.46	1.35	1.35	1.24	1.18	1.07	1.13	1.01
315.0	1.24	1.18	1.13	1.13	1.13	1.07	1.01	1.01	1.01
360.0	1.52	1.41	1.35	1.35	1.24	1.24	1.13	1.13	1.13
C/ γ (°)	81.0	82.0	83.0	84.0	85.0	86.0	87.0	88.0	89.0
0.0	1.01	1.01	1.01	0.96	0.84	0.73	0.68	0.62	0.62
45.0	2.08	1.91	1.63	1.18	0.96	0.79	0.68	0.51	0.39
90.0	0.84	0.84	0.79	0.62	0.56	0.51	0.51	0.39	0.39
135.0	1.01	1.01	0.96	0.96	0.84	0.90	0.84	0.73	0.68
180.0	1.58	1.46	1.41	1.35	1.18	1.18	1.13	1.01	0.90
225.0	1.52	1.46	1.35	1.24	1.07	1.01	0.73	0.62	0.51
270.0	0.96	0.90	0.73	0.68	0.68	0.68	0.68	0.56	0.51
315.0	0.96	0.90	0.96	0.90	0.90	0.79	0.73	0.68	0.62
360.0	1.01	1.01	1.01	0.96	0.84	0.73	0.68	0.62	0.62

Intensity data(cd)

C/ $\gamma(^{\circ})$	90.0
0.0	0.62
45.0	0.34
90.0	0.39
135.0	0.73
180.0	0.73
225.0	0.51
270.0	0.51
315.0	0.68
360.0	0.62