



NATA LIGHTING CO.,LTD
www.nata.cn
Email:info@nata.cn
Tel:+86 0750-377 0000(10 lines) Fax:+86 0750-377 1111
Address:380JinOu Road,Gaoxin Zone,Jiang Men City,Guangdong,China

NT

Client: NT

LumCAT: 1-1760-LM2

Luminaire: 92.70.492.00 LED HOLDER

Report No: 20251218-B010

Ballast type: AC

Test No: 20251218-C010

Voltage(V): 35.080

LampCAT: CITIZEN CLU028 LES9.8

Current(A): 0.362

Lamp flux(lm): 1573.0

Power (W): 12.698

Number of Lamps: 1

PF: 0.000

Length(mm): 50

Width(mm): 50

Phm Type: C

Height(mm): 22

Photometric Results

Lumens(lm): 1519.46, Efficiency(%): 96.60% , Luminous Efficacy(lm/W): 119.66

Central intensity(cd): 2698.397, Maximum intensity(cd): 2698.397

Angle of maximum intensity: C=0.0 γ =0.0

Beam Angle(50%Imax): [C0/180]Total=35.8

[C90/270]Total=35.8

Field angle(10%Imax): [C0/180]Total=85.0

[C90/270]Total=85.0

Maximum s/h(1/2): C0_180=0.60 C90_270=0.60

Maximum s/h(1/4): C0_180=0.62 C90_270=0.62

Up flux rate of lamp(%): 0.00%


Down flux rate of lamp(%): 96.60%


Up flux rate of LUM(%): - -


Down flux rate of LUM(%): 100.00%

CIE Type : Direct lighting

Output flux ratio in π solid angle : 99.920%








House


[Unit:cd]

Road

Imax:2698.40	
(10%Imax) 269.84	—
(20%Imax) 539.679	—
(30%Imax) 809.519	—
(40%Imax) 1079.36	—
(50%Imax) 1349.2	—
(60%Imax) 1619.04	—
(70%Imax) 1888.88	—
(80%Imax) 2158.72	—
(90%Imax) 2428.56	—



(10%Emax)	67.46	
(20%Emax)	134.9198	
(30%Emax)	202.3797	
(40%Emax)	269.84	
(50%Emax)	337.3	
(60%Emax)	404.76	
(70%Emax)	472.22	
(80%Emax)	539.68	
(90%Emax)	607.14	



Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	85540	9674	4634	1198	692	493	413	356	452
C45	85540	9674	4634	1198	692	493	413	356	452
C90	85540	9674	4634	1198	692	493	413	356	452

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
692	692	692	413	413	413	452	452	452

Glare Table


Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve




Illumination assessment according UGR											
Rf of Ceiling		70	70	50	50	30	70	70	50	50	30
Rf of Wall		50	30	50	30	30	50	30	50	30	30
Rf of Floor		20	20	20	20	20	20	20	20	20	20
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	23.94	24.94	24.31	25.25	25.57	23.81	24.80	24.17	25.11	25.43
	3H	23.74	24.62	24.13	24.96	25.30	23.60	24.48	23.99	24.82	25.17
	4H	23.64	24.45	24.04	24.80	25.17	23.50	24.31	23.90	24.67	25.03
	6H	23.55	24.29	23.97	24.67	25.07	23.41	24.15	23.83	24.53	24.93
	8H	23.47	24.18	23.89	24.57	24.97	23.34	24.04	23.76	24.43	24.84
	12H	23.40	24.07	23.83	24.47	24.88	23.26	23.93	23.69	24.33	24.75
4H	2H	23.64	24.45	24.04	24.80	25.17	23.50	24.31	23.90	24.67	25.04
	3H	23.40	24.07	23.82	24.47	24.88	23.26	23.93	23.69	24.33	24.75
	4H	23.32	23.90	23.76	24.32	24.77	23.18	23.76	23.62	24.19	24.64
	6H	23.18	23.69	23.65	24.14	24.59	23.04	23.55	23.51	24.00	24.45
	8H	23.11	23.59	23.60	24.04	24.52	22.98	23.45	23.46	23.91	24.38
	12H	23.06	23.50	23.55	23.95	24.47	22.92	23.36	23.41	23.81	24.33
8H	4H	23.11	23.59	23.60	24.04	24.52	22.98	23.45	23.46	23.91	24.38
	6H	22.95	23.34	23.46	23.82	24.33	22.82	23.20	23.32	23.68	24.19
	8H	22.93	23.26	23.47	23.78	24.28	22.80	23.12	23.33	23.64	24.14
	12H	22.87	23.13	23.42	23.64	24.17	22.74	22.99	23.28	23.51	24.03
12H	4H	23.06	23.50	23.55	23.95	24.47	22.92	23.36	23.41	23.81	24.33
	6H	22.93	23.26	23.47	23.78	24.28	22.80	23.12	23.33	23.64	24.14
	8H	22.87	23.13	23.42	23.64	24.17	22.74	22.99	23.28	23.51	24.03
Variation with the observer position at spacings:											
S = 1.0H		3.4/-19.7					3.4/-19.7				
S = 1.5H		5.5/-27.0					5.5/-27.0				
S = 2.0H		7.5/-28.2					7.5/-28.2				
Standard tables:		BK0					BK0				
Uncorrected UGR		4.6					4.6				

UGR calculation is based on CIE Publ. 117 ,S/H = 0.25



RHOC	80			70			50			30			10			0
RHOW	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	COEFFICIENTS OF UTILIZATION RHOFC=20 CU															
0	1.15	1.15	1.15	1.12	1.12	1.12	1.07	1.07	1.07	1.03	1.03	1.03	0.99	0.99	0.99	0.97
1	1.07	1.05	1.03	1.05	1.03	1.01	1.01	1.00	0.98	0.98	0.96	0.95	0.94	0.93	0.93	0.91
2	1.00	0.96	0.93	0.99	0.95	0.92	0.95	0.93	0.90	0.93	0.90	0.88	0.90	0.88	0.87	0.85
3	0.94	0.89	0.86	0.92	0.88	0.85	0.90	0.86	0.83	0.88	0.85	0.82	0.85	0.83	0.81	0.79
4	0.88	0.83	0.79	0.87	0.82	0.78	0.85	0.81	0.78	0.83	0.79	0.77	0.81	0.78	0.76	0.74
5	0.83	0.77	0.73	0.82	0.77	0.73	0.80	0.76	0.72	0.79	0.75	0.72	0.77	0.74	0.71	0.70
6	0.78	0.72	0.68	0.77	0.72	0.68	0.76	0.71	0.68	0.74	0.70	0.67	0.73	0.70	0.67	0.66
7	0.74	0.68	0.64	0.73	0.68	0.64	0.72	0.67	0.64	0.71	0.66	0.63	0.70	0.66	0.63	0.62
8	0.70	0.64	0.60	0.69	0.64	0.60	0.68	0.63	0.60	0.67	0.63	0.60	0.66	0.62	0.60	0.58
9	0.66	0.61	0.57	0.66	0.60	0.57	0.65	0.60	0.57	0.64	0.60	0.57	0.63	0.59	0.56	0.55
10	0.63	0.58	0.54	0.62	0.57	0.54	0.62	0.57	0.54	0.61	0.57	0.54	0.60	0.56	0.53	0.52



Luminaire Lumens:

FL=527.47,FM=214.34,FH=0.54,FVH=0.06

BL=543.99,BM=221.96,BH=0.51,BVH=0.06

UL=0,UH=0

BUG Rating:B2-U0-G0

Intensity data(cd)

C/γ(°)	0.0	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0
0.0	2698.26	2679.69	2664.51	2634.13	2593.63	2543.01	2471.01	2429.38	2320.82
45.0	2698.82	2697.69	2688.13	2676.88	2646.51	2595.32	2567.19	2502.51	2437.82
90.0	2700.51	2689.26	2670.13	2634.69	2611.63	2566.07	2510.38	2444.01	2348.38
135.0	2696.01	2698.26	2691.51	2667.88	2653.82	2613.88	2568.88	2514.88	2447.94
180.0	2698.26	2703.88	2699.94	2683.07	2660.01	2626.82	2584.63	2554.26	2485.07
225.0	2698.82	2690.94	2670.13	2654.38	2621.19	2579.57	2528.94	2454.13	2382.69
270.0	2700.51	2703.32	2699.94	2685.88	2665.07	2635.26	2586.32	2533.44	2469.88
315.0	2696.01	2685.88	2666.76	2639.76	2593.63	2565.51	2509.26	2441.19	2344.44
360.0	2698.26	2679.69	2664.51	2634.13	2593.63	2543.01	2471.01	2429.38	2320.82

C/γ(°)	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0
0.0	2213.94	2175.69	2055.88	1950.13	1840.44	1707.69	1640.19	1529.38	1422.51
45.0	2364.13	2283.13	2230.26	2117.19	2015.38	1909.63	1801.63	1736.38	1562.01
90.0	2257.26	2156.01	2023.82	1954.07	1833.69	1709.94	1585.07	1439.94	1369.07
135.0	2402.94	2301.69	2206.07	2100.32	1986.69	1915.26	1769.57	1646.94	1522.63
180.0	2417.01	2339.94	2254.44	2199.32	2081.76	1936.07	1870.82	1759.44	1626.13
225.0	2302.26	2195.94	2138.57	2037.88	1932.13	1824.13	1692.51	1626.13	1515.32
270.0	2395.07	2345.01	2232.51	2128.44	2016.51	1898.38	1825.82	1676.76	1503.51
315.0	2252.76	2193.13	2041.26	1898.94	1825.82	1701.51	1577.76	1454.57	1311.69
360.0	2213.94	2175.69	2055.88	1950.13	1840.44	1707.69	1640.19	1529.38	1422.51

C/γ(°)	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0
0.0	1319.01	1083.26	1083.26	1049.91	958.16	916.31	852.64	796.56	747.56
45.0	1454.01	1392.69	1274.57	1181.76	1095.13	1014.69	970.82	890.38	831.88
90.0	1116.79	1077.69	1058.79	970.76	892.46	823.84	753.13	722.59	677.93
135.0	1378.63	1263.32	1155.88	1056.88	1002.32	902.76	830.76	768.88	715.44
180.0	1516.44	1409.57	1346.57	1226.19	1133.38	1047.32	969.13	925.26	845.94
225.0	1407.32	1304.38	1070.38	1070.38	1036.86	944.33	902.19	839.42	752.40
270.0	1430.94	1313.94	1182.32	1081.07	989.38	938.76	848.76	783.51	727.26
315.0	1104.36	1104.36	1010.14	957.83	878.40	809.16	749.64	690.02	664.03
360.0	1319.01	1083.26	1083.26	1049.91	958.16	916.31	852.64	796.56	747.56

C/γ(°)	27.0	28.0	29.0	30.0	31.0	32.0	33.0	34.0	35.0
0.0	696.83	674.16	627.53	593.61	578.70	555.92	534.71	515.70	495.11
45.0	779.57	733.44	708.13	663.69	631.63	602.94	573.13	551.76	530.94
90.0	619.76	601.54	574.37	550.91	531.34	510.81	501.41	486.84	473.51
135.0	687.32	623.76	592.26	577.07	552.32	527.57	510.13	493.82	485.94
180.0	788.57	738.51	695.19	671.57	615.88	587.19	571.44	543.88	523.07
225.0	723.88	681.47	658.41	612.23	578.98	564.02	541.07	519.81	500.57
270.0	680.01	654.69	611.94	570.88	556.82	530.94	523.07	495.51	480.88
315.0	626.23	594.56	567.90	540.68	521.16	504.34	486.51	478.41	465.69
360.0	696.83	674.16	627.53	593.61	578.70	555.92	534.71	515.70	495.11

C/γ(°)	36.0	37.0	38.0	39.0	40.0	41.0	42.0	43.0	44.0
0.0	484.54	462.04	431.38	394.31	341.16	313.37	245.42	216.00	158.46
45.0	511.82	501.13	476.94	448.82	413.38	371.76	344.76	297.51	297.51
90.0	461.08	438.47	421.43	388.46	348.41	297.96	253.91	208.01	163.86
135.0	470.19	457.82	443.76	420.13	401.57	357.69	299.76	290.76	290.76
180.0	504.51	487.63	476.94	449.38	417.88	380.19	326.76	308.19	308.19
225.0	479.31	466.65	439.14	403.71	354.32	308.70	260.83	212.63	156.04
270.0	472.44	457.26	440.38	414.51	381.88	359.38	309.88	292.44	292.44
315.0	454.05	436.16	401.06	379.63	323.83	270.96	253.07	199.86	155.93
360.0	484.54	462.04	431.38	394.31	341.16	313.37	245.42	216.00	158.46

Intensity data(cd)

C/ γ (°)	45.0	46.0	47.0	48.0	49.0	50.0	51.0	52.0	53.0
0.0	114.02	75.77	45.34	22.44	16.43	12.88	10.63	8.89	7.37
45.0	198.17	141.98	99.96	62.89	31.73	18.90	14.46	11.98	10.69
90.0	113.74	90.51	56.14	29.64	15.24	10.52	9.56	7.71	6.58
135.0	182.93	139.50	99.06	76.84	30.32	15.81	11.53	9.56	8.21
180.0	180.96	162.28	109.52	72.11	42.75	21.88	14.46	12.54	10.69
225.0	129.54	88.76	54.28	30.04	16.71	14.96	12.94	10.91	9.62
270.0	175.73	133.09	92.81	52.37	41.34	18.73	11.64	10.63	8.72
315.0	114.64	70.03	50.51	26.38	14.23	10.69	8.78	7.99	7.14
360.0	114.02	75.77	45.34	22.44	16.43	12.88	10.63	8.89	7.37
C/ γ (°)	54.0	55.0	56.0	57.0	58.0	59.0	60.0	61.0	62.0
0.0	6.36	5.34	2.81	2.42	2.19	1.86	1.63	1.41	1.18
45.0	8.83	7.54	6.47	5.23	3.60	2.76	2.36	2.08	1.86
90.0	6.30	5.34	3.99	1.58	1.41	1.24	1.18	1.07	0.90
135.0	7.20	6.36	5.85	4.44	1.69	1.41	1.24	1.18	1.01
180.0	9.90	8.55	7.48	6.08	2.48	1.97	1.74	1.46	1.41
225.0	8.44	7.31	4.78	2.19	2.03	1.74	1.52	1.29	1.13
270.0	7.82	7.09	6.24	5.40	1.52	1.29	1.18	1.07	0.90
315.0	6.02	5.63	3.88	1.63	1.29	1.18	1.13	0.96	0.79
360.0	6.36	5.34	2.81	2.42	2.19	1.86	1.63	1.41	1.18
C/ γ (°)	63.0	64.0	65.0	66.0	67.0	68.0	69.0	70.0	71.0
0.0	1.07	0.90	0.79	0.73	0.62	0.51	0.45	0.45	0.39
45.0	1.52	1.29	1.07	0.96	0.79	0.73	0.68	0.62	0.56
90.0	0.73	0.68	0.56	0.56	0.51	0.45	0.39	0.28	0.34
135.0	0.84	0.79	0.62	0.62	0.56	0.51	0.51	0.39	0.34
180.0	1.13	0.96	0.84	0.73	0.73	0.56	0.56	0.51	0.45
225.0	0.96	0.84	0.73	0.62	0.62	0.56	0.45	0.39	0.39
270.0	0.79	0.68	0.62	0.51	0.51	0.45	0.39	0.39	0.34
315.0	0.68	0.62	0.62	0.51	0.45	0.45	0.39	0.34	0.28
360.0	1.07	0.90	0.79	0.73	0.62	0.51	0.45	0.45	0.39
C/ γ (°)	72.0	73.0	74.0	75.0	76.0	77.0	78.0	79.0	80.0
0.0	0.39	0.28	0.28	0.28	0.28	0.23	0.17	0.17	0.17
45.0	0.45	0.34	0.39	0.34	0.28	0.23	0.23	0.17	0.23
90.0	0.28	0.28	0.23	0.23	0.17	0.17	0.17	0.11	0.11
135.0	0.39	0.28	0.28	0.28	0.23	0.23	0.23	0.17	0.17
180.0	0.39	0.39	0.34	0.34	0.28	0.23	0.23	0.23	0.17
225.0	0.34	0.28	0.28	0.23	0.23	0.23	0.11	0.11	0.11
270.0	0.28	0.28	0.23	0.23	0.17	0.11	0.17	0.11	0.11
315.0	0.28	0.28	0.23	0.23	0.17	0.23	0.17	0.11	0.17
360.0	0.39	0.28	0.28	0.28	0.28	0.23	0.17	0.17	0.17
C/ γ (°)	81.0	82.0	83.0	84.0	85.0	86.0	87.0	88.0	89.0
0.0	0.11	0.17	0.11	0.11	0.11	0.11	0.11	0.17	0.11
45.0	0.11	0.11	0.11	0.11	0.11	0.06	0.06	0.06	0.06
90.0	0.11	0.06	0.11	0.06	0.06	0.06	0.06	0.00	0.06
135.0	0.23	0.17	0.17	0.17	0.17	0.23	0.28	0.34	0.28
180.0	0.17	0.17	0.11	0.11	0.06	0.17	0.17	0.17	0.23
225.0	0.11	0.06	0.11	0.06	0.06	0.06	0.11	0.06	0.00
270.0	0.11	0.11	0.11	0.06	0.06	0.00	0.00	0.00	0.06
315.0	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.23	0.23
360.0	0.11	0.17	0.11	0.11	0.11	0.11	0.11	0.17	0.11

Intensity data(cd)

C/ $\gamma(^{\circ})$	90.0
0.0	0.11
45.0	0.06
90.0	0.11
135.0	0.28
180.0	0.17
225.0	0.06
270.0	0.06
315.0	0.23
360.0	0.11