



NATA LIGHTING CO.,LTD
www.nata.cn
Email:info@nata.cn
Tel:+86 0750-377 0000(10 lines) Fax:+86 0750-377 1111
Address:380JinOu Road,Gaoxin Zone,Jiang Men City,Guangdong,China

NT

Client: NT

LumCAT: 2-3118-LM

Luminaire: 92.70.412.00 LED HOLDER

Report No: 20260123-B008

Ballast type: AC

Test No: 20260123-C008

Voltage(V): 36.820

LampCAT: CITIZEN CLU038 LES14.5

Current(A): 0.712

Lamp flux(lm): 3448.0

Power (W): 26.218

Number of Lamps: 1

PF: 0.000

Length(mm): 65

Width(mm): 65

Phm Type: C

Height(mm): 34

Photometric Results

Lumens(lm): 3317.56, Efficiency(%): 96.22% , Luminous Efficacy(lm/W): 126.54

Central intensity(cd): 16476.750, Maximum intensity(cd): 16476.750

Angle of maximum intensity: C=0.0 γ =0.0

Beam Angle(50%Imax): [C0/180]Total=19.2

[C90/270]Total=19.2

Field angle(10%Imax): [C0/180]Total=42.4

[C90/270]Total=42.4

Maximum s/h(1/2): C0_180=0.33 C90_270=0.33

Maximum s/h(1/4): C0_180=0.33 C90_270=0.33

Up flux rate of lamp(%): 0.00%


Down flux rate of lamp(%): 96.22%


Up flux rate of LUM(%): - -


Down flux rate of LUM(%): 100.00%

CIE Type : Direct lighting

Output flux ratio in π solid angle : 99.996%








House


[Unit:cd]

Road

Imax:16476.75	
(10%Imax) 1647.68	
(20%Imax) 3295.35	
(30%Imax) 4943.02	
(40%Imax) 6590.7	
(50%Imax) 8238.38	
(60%Imax) 9886.05	
(70%Imax) 11533.7	
(80%Imax) 13181.4	
(90%Imax) 14829.1	



(10%Emax)	411.9175	
(20%Emax)	823.8375	
(30%Emax)	1235.755	
(40%Emax)	1647.675	
(50%Emax)	2059.593	
(60%Emax)	2471.51	
(70%Emax)	2883.425	
(80%Emax)	3295.35	
(90%Emax)	3707.275	



Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	10531	1088	222	98	29	0	0	0	0
C45	9486	967	195	85	25	0	0	0	0
C90	10531	1088	222	98	29	0	0	0	0

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
52	52	52	0	0	0	0	0	0

Glare Table


Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve




Illumination assessment according UGR											
Rf of Ceiling		70	70	50	50	30	70	70	50	50	30
Rf of Wall		50	30	50	30	30	50	30	50	30	30
Rf of Floor		20	20	20	20	20	20	20	20	20	20
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	19.59	20.50	19.95	20.81	21.13	19.86	20.77	20.22	21.08	21.40
	3H	19.37	20.18	19.76	20.51	20.86	19.64	20.45	20.03	20.79	21.13
	4H	19.26	20.00	19.66	20.36	20.73	19.53	20.27	19.93	20.63	21.00
	6H	19.16	19.84	19.58	20.22	20.62	19.44	20.11	19.86	20.49	20.89
	8H	19.09	19.73	19.51	20.12	20.53	19.36	20.00	19.78	20.39	20.80
	12H	19.01	19.62	19.44	20.02	20.44	19.28	19.89	19.71	20.29	20.71
4H	2H	19.26	20.00	19.66	20.36	20.73	19.53	20.27	19.93	20.63	21.00
	3H	19.00	19.62	19.43	20.02	20.43	19.27	19.89	19.70	20.29	20.71
	4H	18.91	19.45	19.35	19.87	20.32	19.18	19.72	19.62	20.14	20.59
	6H	18.76	19.23	19.24	19.69	20.14	19.03	19.50	19.51	19.96	20.41
	8H	18.70	19.13	19.19	19.59	20.07	18.97	19.40	19.46	19.86	20.34
	12H	18.64	19.04	19.13	19.50	20.02	18.91	19.31	19.40	19.77	20.29
8H	4H	18.70	19.13	19.19	19.59	20.07	18.97	19.40	19.46	19.86	20.34
	6H	18.53	18.89	19.04	19.37	19.88	18.80	19.16	19.31	19.64	20.15
	8H	18.51	18.80	19.05	19.33	19.83	18.78	19.08	19.32	19.60	20.10
	12H	18.45	18.67	19.00	19.19	19.72	18.72	18.94	19.27	19.46	19.99
12H	4H	18.64	19.04	19.13	19.50	20.02	18.91	19.31	19.40	19.77	20.29
	6H	18.51	18.80	19.05	19.33	19.83	18.78	19.08	19.32	19.60	20.10
	8H	18.45	18.67	19.00	19.19	19.72	18.72	18.94	19.27	19.46	19.99
Variation with the observer position at spacings:											
S = 1.0H		4.8/-35.1					4.8/-35.1				
S = 1.5H		7.7/-42.9					7.7/-42.9				
S = 2.0H		9.7/-60.3					9.7/-60.3				
Standard tables:		BK0					BK0				
Uncorrected UGR		0.0					0.0				

UGR calculation is based on CIE Publ. 117 ,S/H = 0.25



RHOCC	80			70			50			30			10			0
RHOW	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	COEFFCIENTS OF UTILIZATION RHOFC=20 CU															
0	1.15	1.15	1.15	1.12	1.12	1.12	1.07	1.07	1.07	1.02	1.02	1.02	0.98	0.98	0.98	0.96
1	1.08	1.06	1.04	1.06	1.04	1.03	1.02	1.01	1.00	0.99	0.98	0.97	0.95	0.95	0.94	0.92
2	1.02	0.99	0.97	1.01	0.98	0.95	0.98	0.95	0.93	0.95	0.93	0.91	0.92	0.91	0.90	0.88
3	0.97	0.93	0.90	0.96	0.92	0.90	0.94	0.91	0.88	0.91	0.89	0.87	0.89	0.87	0.86	0.84
4	0.93	0.89	0.85	0.92	0.88	0.85	0.90	0.86	0.84	0.88	0.85	0.83	0.86	0.84	0.82	0.81
5	0.89	0.84	0.81	0.88	0.84	0.81	0.86	0.83	0.80	0.85	0.82	0.79	0.83	0.81	0.79	0.77
6	0.85	0.80	0.77	0.84	0.80	0.77	0.83	0.79	0.77	0.82	0.78	0.76	0.81	0.78	0.76	0.74
7	0.82	0.77	0.74	0.81	0.77	0.74	0.80	0.76	0.73	0.79	0.76	0.73	0.78	0.75	0.73	0.72
8	0.79	0.74	0.71	0.78	0.74	0.71	0.77	0.73	0.71	0.76	0.73	0.70	0.75	0.72	0.70	0.69
9	0.76	0.71	0.68	0.75	0.71	0.68	0.75	0.71	0.68	0.74	0.70	0.68	0.73	0.70	0.68	0.67
10	0.73	0.69	0.66	0.73	0.69	0.66	0.72	0.68	0.66	0.72	0.68	0.66	0.71	0.68	0.66	0.65



Luminaire Lumens:

FL=1353.96,FM=287.78,FH=0.07,FVH=0

BL=1377.69,BM=291.17,BH=0.06,BVH=0

UL=0,UH=0

BUG Rating:B3-U0-G0

Intensity data(cd)

Appendix Page: 12 Total:14

C/γ(°)	0.0	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0
0.0	16516.13	16381.13	16054.88	15537.38	14609.25	13585.50	10382.57	10382.57	10087.82
45.0	16369.88	16544.25	16572.38	16510.50	16133.63	15638.63	14913.00	13956.75	13276.13
90.0	16639.88	16651.13	16516.13	16223.63	15734.25	14851.13	13855.50	10581.13	10581.13
135.0	16381.13	16493.63	16493.63	16173.00	15762.38	15408.00	14491.13	13461.75	12201.75
180.0	16516.13	16510.50	16324.88	15981.75	15453.00	14699.25	14153.63	12820.50	11476.13
225.0	16369.88	16026.75	15368.63	14924.25	14013.00	10099.07	10099.07	10099.07	8614.63
270.0	16639.88	16482.38	16128.00	15633.00	14896.13	14350.50	12994.88	11088.00	10210.50
315.0	16381.13	16071.75	15576.75	14693.63	14125.50	11133.51	10543.44	10243.63	8764.82
360.0	16516.13	16381.13	16054.88	15537.38	14609.25	13585.50	10382.57	10382.57	10087.82
C/γ(°)	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0
0.0	8034.69	6434.38	5753.19	4794.69	4030.26	3423.88	2876.57	2654.94	2346.69
45.0	11684.25	9603.00	8686.13	6959.25	5716.13	4720.50	3949.88	3573.00	2959.88
90.0	10271.19	8109.51	7248.88	5967.51	4740.69	3968.94	3373.82	2829.32	2609.94
135.0	10773.00	9873.00	8101.13	6739.88	5564.25	4624.88	4163.63	3409.88	2931.75
180.0	10013.63	8247.38	6891.75	5699.25	4748.63	4276.13	3511.13	3016.13	2847.38
225.0	6967.07	5783.57	5181.13	4051.07	3344.01	3066.13	2679.69	2366.38	2113.82
270.0	8455.50	7060.50	5856.75	4878.00	4388.63	3595.50	3094.88	2920.50	2841.75
315.0	7378.82	6150.88	4956.69	4461.13	3784.44	3253.44	2828.76	2432.76	2169.51
360.0	8034.69	6434.38	5753.19	4794.69	4030.26	3423.88	2876.57	2654.94	2346.69
C/γ(°)	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0
0.0	2093.57	1884.32	1685.76	1604.19	1447.26	1344.32	1301.01	1240.26	1187.94
45.0	2959.88	2796.75	2071.07	1868.01	1702.63	1569.32	1498.44	1383.69	1307.19
90.0	2305.07	2062.07	1861.82	1669.44	1589.01	1433.76	1330.26	1286.94	1227.32
135.0	2931.75	2275.82	2031.13	1831.44	1641.88	1587.88	1449.51	1328.01	1286.94
180.0	2587.44	2107.07	1898.94	1725.69	1639.07	1491.69	1394.38	1314.51	1249.82
225.0	1874.76	1772.94	1625.01	1503.51	1385.38	1308.88	1245.32	1193.57	1110.71
270.0	2159.94	1951.26	1774.63	1682.38	1527.69	1391.57	1343.76	1274.01	1239.13
315.0	1951.82	1739.76	1653.13	1525.44	1421.94	1339.82	1261.63	1227.32	1107.68
360.0	2093.57	1884.32	1685.76	1604.19	1447.26	1344.32	1301.01	1240.26	1187.94
C/γ(°)	27.0	28.0	29.0	30.0	31.0	32.0	33.0	34.0	35.0
0.0	1112.18	1112.18	1091.31	1048.84	1019.36	998.83	945.17	875.36	795.49
45.0	1243.07	1180.07	1136.19	1097.94	1065.32	1047.88	1017.51	984.32	934.26
90.0	1189.07	1100.81	1100.81	1068.41	1041.64	1009.80	987.81	934.48	870.98
135.0	1218.32	1167.13	1121.01	1085.01	1066.44	1032.69	1007.38	970.82	900.51
180.0	1186.26	1137.88	1098.51	1078.26	1043.94	1018.07	983.76	926.38	886.44
225.0	1110.71	1088.83	1057.73	1027.13	993.60	941.12	872.72	777.71	728.38
270.0	1153.07	1112.01	1089.51	1051.82	1026.51	994.44	944.94	911.19	825.69
315.0	1107.68	1100.48	1066.73	1040.40	1012.67	960.02	894.21	817.14	716.01
360.0	1112.18	1112.18	1091.31	1048.84	1019.36	998.83	945.17	875.36	795.49
C/γ(°)	36.0	37.0	38.0	39.0	40.0	41.0	42.0	43.0	44.0
0.0	696.32	643.44	553.61	462.09	351.45	264.99	217.74	115.09	48.04
45.0	866.19	821.19	721.07	633.32	540.51	447.13	335.76	299.19	299.19
90.0	793.74	688.39	633.71	536.85	434.59	337.56	230.51	184.39	88.59
135.0	825.69	744.69	656.94	605.19	496.07	403.82	314.94	314.94	149.12
180.0	794.76	710.94	627.13	534.88	480.88	336.32	336.32	336.32	131.23
225.0	639.39	544.73	450.00	337.33	251.21	170.61	89.38	67.28	23.46
270.0	742.44	653.57	539.94	498.88	380.19	339.69	339.69	125.38	52.03
315.0	662.34	572.40	476.94	385.03	279.39	228.15	149.85	84.09	37.63
360.0	696.32	643.44	553.61	462.09	351.45	264.99	217.74	115.09	48.04

Intensity data(cd)

C/γ(°)	45.0	46.0	47.0	48.0	49.0	50.0	51.0	52.0	53.0
0.0	26.89	11.14	8.72	6.64	5.01	4.56	3.32	1.52	1.18
45.0	137.42	46.35	19.18	11.25	7.93	6.13	4.89	3.94	3.21
90.0	36.73	21.15	9.79	8.21	6.53	5.29	4.84	3.43	1.46
135.0	82.86	37.13	21.60	9.73	8.10	6.30	5.29	4.67	2.08
180.0	49.78	27.84	10.63	8.66	6.81	5.57	5.01	3.32	1.58
225.0	10.07	8.04	5.85	5.06	4.22	3.04	1.52	1.13	0.96
270.0	29.76	9.96	7.82	5.96	4.61	4.11	2.76	1.52	1.29
315.0	12.88	9.06	7.20	4.67	4.16	3.15	1.80	1.24	0.96
360.0	26.89	11.14	8.72	6.64	5.01	4.56	3.32	1.52	1.18

C/γ(°)	54.0	55.0	56.0	57.0	58.0	59.0	60.0	61.0	62.0
0.0	0.96	0.73	0.62	0.62	0.51	0.45	0.39	0.23	0.23
45.0	1.46	1.29	1.07	0.90	0.84	0.68	0.56	0.51	0.45
90.0	1.29	1.01	0.79	0.73	0.62	0.56	0.45	0.39	0.34
135.0	1.35	1.24	0.96	0.79	0.62	0.56	0.51	0.39	0.39
180.0	1.29	1.01	0.90	0.68	0.56	0.45	0.39	0.28	0.23
225.0	0.68	0.56	0.51	0.34	0.34	0.28	0.17	0.17	0.11
270.0	0.96	0.84	0.68	0.51	0.51	0.34	0.28	0.23	0.11
315.0	0.79	0.68	0.56	0.45	0.39	0.28	0.28	0.17	0.11
360.0	0.96	0.73	0.62	0.62	0.51	0.45	0.39	0.23	0.23

C/γ(°)	63.0	64.0	65.0	66.0	67.0	68.0	69.0	70.0	71.0
0.0	0.17	0.11	0.11	0.06	0.00	0.00	0.00	0.00	0.00
45.0	0.34	0.23	0.28	0.17	0.11	0.06	0.06	0.00	0.00
90.0	0.23	0.23	0.11	0.11	0.06	0.00	0.00	0.00	0.00
135.0	0.28	0.23	0.17	0.11	0.06	0.06	0.00	0.00	0.00
180.0	0.17	0.17	0.11	0.06	0.00	0.00	0.00	0.00	0.00
225.0	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
270.0	0.11	0.06	0.06	0.00	0.00	0.00	0.00	0.00	0.00
315.0	0.11	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.00
360.0	0.17	0.11	0.11	0.06	0.00	0.00	0.00	0.00	0.00

C/γ(°)	72.0	73.0	74.0	75.0	76.0	77.0	78.0	79.0	80.0
0.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
45.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
135.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
225.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
270.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
315.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
360.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C/γ(°)	81.0	82.0	83.0	84.0	85.0	86.0	87.0	88.0	89.0
0.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
45.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
135.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
225.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
270.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
315.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
360.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Intensity data(cd)

C/ $\gamma(^{\circ})$	90.0
0.0	0.00
45.0	0.00
90.0	0.00
135.0	0.00
180.0	0.00
225.0	0.00
270.0	0.00
315.0	0.00
360.0	0.00