



NATA LIGHTING CO.,LTD.
www.nata.cn
Email:info@nata.com
Tel:+86-750-3770000 Fax:+86-750-3771111
Address:380JinOu Road,GaoXin Zone,Jiang Men City,Guangdong,China

Nata

LumCAT:3-1943-M

Luminaire:

Report No: NATA0100

Test No: GC2019082601

LampCAT: TRIDONIC SLE G7 22MM

Lamp flux(lm): 1837.0

Number of Lamps: 1

Length(mm): 0

Phm Type: C

Voltage(V): 34.5600

Current(A): 0.6470

Power (W): 22.3600

PF: 0.0000

Ballast type: AC

Width(mm): 0

Height(mm): 0

Photometric Results

Lumens(lm): 1551.35

Efficiency(%): 84.45%

Lumens(lm)/Power(W): 69.38

Central intensity(cd): 4245.609

Maximum intensity(cd): 4245.609

Angle of maximum intensity: C=0.0 γ =0.0

Beam Angle(50%Imax): [C0/180]Total=30.7

[C90/270]Total=30.7

Field angle(10%Imax): [C0/180]Total=64.6

[C90/270]Total=64.6

Maximum s/h(1/2): C0_180=0.52 C90_270=0.52

Maximum s/h(1/4): C0_180=0.50 C90_270=0.50

Up flux rate of lamp(%): 0.00%

Down flux rate of lamp(%): 84.45%

Up flux rate of LUM(%): - -

Down flux rate of LUM(%): 100.00%

CIE Type : Direct lighting

Output flux ratio in π solid angle : 98.337%

