



NATA LIGHTING CO.,LTD.  
www.nata.cn  
Email:info@nata.com  
Tel:+86-750-3770000 Fax:+86-750-3771111  
Address:380JinOu Road,GaoXin Zone,Jiang Men City,Guangdong,China

---

## Nata

---

LumCAT: 3-2033-M2  
Luminaire: 92.70.135.00+92.70.153.00  
Report No: 200922-B014  
Test No: 200922-C014  
LampCAT: Vesta DW LES15 Gen2 PD  
Lamp flux(lm): 1618.0  
Number of Lamps: 1  
Length(mm): 0  
Phm Type: C



Voltage(V): 32.9400  
Current(A): 0.4520  
Power (W): 14.8880  
PF: 0.0000  
Ballast type: DC  
Width(mm): 0  
Height(mm): 0

---

## Photometric Results

---

Lumens(lm): 1293.79  
Efficiency(%): 79.96%  
Lumens(lm)/Power(W): 86.90  
Central intensity(cd): 5739.047  
Maximum intensity(cd): 5739.047  
Angle of maximum intensity: C=0.0  $\gamma$ =0.0  
Beam Angle(50%Imax): [C0/180]Total=18.1  
                                  [C90/270]Total=18.1  
Field angle(10%Imax): [C0/180]Total=53.1  
                                  [C90/270]Total=53.1  
Maximum s/h(1/2): C0\_180=0.31 C90\_270=0.31  
Maximum s/h(1/4): C0\_180=0.34 C90\_270=0.34  
Up flux rate of lamp(%): 0.00%  
Down flux rate of lamp(%): 79.96%  
Up flux rate of LUM(%): - -  
Down flux rate of LUM(%): 100.00%  
CIE Type : Direct lighting  
Output flux ratio in  $\pi$  solid angle : 98.594%



C0(Max): —————

C0/C180: —————

C90/C270: —————

Field angle(10%Imax):C0/180Left:26.5 Right:26.5  
:C90/270Left:26.5 Right:26.5

Beam Angle(50%Imax):C0/180Left:9.1 Right:9.1  
:C90/270Left:9.1 Right:9.1