



NATA LIGHTING CO.,LTD.
www.nata.cn
Email:info@nata.com
Tel:+86-750-3770000 Fax:+86-750-3771111
Address:380JinOu Road,GaoXin Zone,Jiang Men City,Guangdong,China

Nata

LumCAT: LN01D05060DA-N

Luminaire: 97.70.234.00

Report No: 200919-B005

Test No: 200919-C005

LampCAT: V6-HD LES7

Lamp flux(lm): 978.9

Number of Lamps: 1

Length(mm): 0

Phm Type: C

Voltage(V): 34.9000

Current(A): 0.2190

Power (W): 7.6430

PF: 0.0000

Ballast type: DC

Width(mm): 0

Height(mm): 0

Photometric Results

Lumens(lm): 841.33

Efficiency(%): 85.95%

Lumens(lm)/Power(W): 110.08

Central intensity(cd): 792.872

Maximum intensity(cd): 798.673

Angle of maximum intensity: C=0.0 γ =5.0

Beam Angle(50%Imax): [C0/180]Total=62.0

[C90/270]Total=62.0

Field angle(10%Imax): [C0/180]Total=91.2

[C90/270]Total=91.2

Maximum s/h(1/2): C0_180=0.95 C90_270=0.95

Maximum s/h(1/4): C0_180=0.93 C90_270=0.93

Up flux rate of lamp(%): 0.00%



Down flux rate of lamp(%): 85.95%

Up flux rate of LUM(%): - -

Down flux rate of LUM(%): 100.00%

CIE Type : Direct lighting

Output flux ratio in π solid angle : 95.966%



C0(Max): —————

C0/C180: —————

C90/C270: —————

Field angle(10%Imax):C0/180Left:50.6 Right:40.6
:C90/270Left:50.6 Right:40.6

Beam Angle(50%Imax):C0/180Left:36.0 Right:26.0
:C90/270Left:36.0 Right:26.0